

TRAILED SARCLERSE



DOWNLOAD
DOCUMENTATION



REQUEST
DEMONSTRATION



FIND A
DEALER



DOWNLOAD
THE NOTICE



PIECE OF
REPLACEMENT

SPRING HARROW

Folding at 3m to drive with serenity

Standard or scissors folding depending on width (scissors from 9m).

Sarclerse are equipped of double tines adapted to your crops and fixed by R clips for a tine quick change.

The mounting system eliminates play (constant elastic pressure mounting) between the tine tube and the double tine. The clip is held tightly against the tube due to the constant tine pressure, which guarantees that the tines are well held.

Spacing between tines : 25mm.

Compact Ø 7mm tines (L = 430 mm or 530 mm) or Ø 8 mm standard (L = 530 mm) for a pasture use.

Manual or hydraulic adjustment of the tines aggressiveness.

Available from 15 to 24m in trailed version !



Hydraulic and mechanic locking safety (transport and work position)



Tine quick change ! Fixation with R clips Manual or hydraulic adjustment of the tines aggressiveness.



THE FRAME

- Trailed chassis, 180x100x10 mm and 100x5 mm tube
- Folding to 2.7 m
- Variable axle track width from 1.7m to 2.25 m with 400-60x15,5 (Ø870x400 mm)
- Folding/unfolding automatic system , sequence by continuous action button.
- Folding pivots with treated steel bushes
- Road light and signals included





THE SECTIONS



Sections independently mounted on parallelograms
Automatic lifting sequence at the end of a bout
Constant pressure over the whole width

IN-CAB CONTROL BOX



A double acting spool valve for all the hydraulic functions

THE WIDTHS: FROM 15 TO 24 M



DOUBLE TINES ADAPTED TO YOUR CROPS !



Rapid tine changing!

The mounting system eliminates play (constant elastic pressure mounting) between the tine tube and the double tine.
The clip is held tightly against the tube due to the constant tine pressure, which guarantees that the tines are well held.



Ø7mm standard(L=530 mm) stimulate vibrations



Ø7 mm compact(L=430 mm) more rigid – less vibrating



Ø 8mm compact (L=530mm) Efficient moss take off



AGGRESSIVITY ADJUSTMENT

Manual adjustment



Hydraulic adjustment



[Discover SARCLERSE](#)

